## T1S R1W DUCHESNE COUNTY MONUMENT SURVEY RECORD N1/16 5/8"X24" REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT SECTION CORNER SEC 30+SEC 29 U.S.B.&M. H-5PIPE FENCE CORNER .59°59'35", W 29 N 79°58'18" E 40.16' NAIL AND WASHER IN LEFT SIDE OF POWER POLE 49.46 S 88°31'02" W PIPE FENCE CORNER 50.80 S 85°22'46" W PIPE FENCE CORNER 00°19'45" NORTH NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N AND LONG. 110"01"46.98583"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' .30' MONUMENT SPIKE

AT 1/4 CORNER

## DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A SURVEY MARKER AND WASHER AT THE POSITION OF THE 1/16 CORNER



SET A SURVEY MARKER AND WASHER AT THE POSITION OF THE 1/16 CORNER



## STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7307221.791 E: 2050074.326 NAVD88 EL: 5583.59'

40°22'15.47479" N LATITUDE: LONGITUDE: 110°01'46.74266" W

ELLIPSOID HEIGHT: *5528.35* '

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0\_200260

## **CERTIFICATION**

Jerry D. Allred \_ , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

